

In the claims:

1. (currently amended) An apparatus for regulating the exciter current for a rotary-current generator, having

- a voltage source,
- a rectifier connected to the voltage source,
- three phase windings connected to the rectifier,
- one evaluation unit connected to one phase winding, and
- one voltage regulator, whose input is connected to the evaluation unit and whose output is connected to the exciter winding of the rotary-current generator,

~~characterized in that~~wherein

the evaluation unit (9) has three input terminals (10, 11, 12), and each of these input terminals is connected to one of the phase windings (5, 6, 7) of the rotary-current generator (2);

the evaluation unit (9) is intended for evaluating the phase voltages associated with the three phase windings, in order to detect unauthorized work states and therefore to detect error functions of the rectifier or error functions of the phase windings; and

the voltage regulator (3) on detecting unauthorized work states reduces the exciter current flowing through the exciter winding (8).

2. (Currently amended) The apparatus of claim 1, ~~characterized in that~~wherein the evaluation unit (9) is a component of the voltage regulator (3).

3. (currently amended) The apparatus of claim 1, ~~characterized in that~~wherein the evaluation unit (9) has a fourth input terminal (14), which is connected to the positive pole of the voltage source (1), and that the evaluation unit has one terminal (15) connected to ground potential.

Claims 4 and 5 cancelled.

6. (Currently amended) The apparatus of claim 1, ~~characterized in that~~wherein the evaluation unit evaluates all three phase voltages for amplitude and/or frequency.